

Standard specifications

PST375-I1

1st Edition: May 25, 2018

KAWASAKI HEAVY INDUSTRIES, LTD.

ROBOT DIVISION

DESIGNED AND MANUFACTURED BY ASTOR LTD.

1. Specification of positioner



- General purpose single axis positioner,
- Vertical rotating axis,
- Used as an external axis with Kawasaki robots (E0x controller),
- Based on Kawasaki components and according to Kawasaki standards,
- Simple/modular body design,
- Hollow shaft – for a direct supply of energy and fluids,
- Lightweight.

2. Technical parameters

Model	PST375-11
Max. payload	375 kg
Degree of freedom	1 axis
Nominal torque	490 Nm
Max. torque	1200 Nm
Max. tilting torque (0 kg)	1750 Nm
Max. tilting torque (with 375kg mounted)	1610 Nm
Turning range	+/-360°*
Max. rotating speed	150°/s
Repeatability	±0.05 mm**
Max. mass moment of inertia	192 kgm ²
Mass	248 kg
Default height of rotating axis	702 mm
Installation	Floor
Color	NCS S 0510-G50Y & RAL9011
Built-in utilities	Welding ground transfer system
Nominal weld current – 100% duty cycle	500 A
Environment cond.	0÷40°C (Humidity) 35÷85%, no dew

*possibility of setup range +/-36000

**on radius r=340mm from rotating axis

3. Dimensions

