Kawasaki Robotics

Standard specifications

PST250


1st Edition: May 25, 2018

KAWASAKI HEAVY INDUSTRIES, LTD.

ROBOT DIVISION

DESIGNED AND MANUFACTURED BY ASTOR LTD.

1. Specification of positioner




- General purpose single axis positioner,
- Horizontal rotating axis,
- Used as an external axis with Kawasaki robots (E0x controller),
- Based on Kawasaki components and according to Kawasaki standards,
- Simple/modular body design,
- Hollow shaft – for a direct supply of energy and fluids,
- Lightweight.


2. Technical parameters


Model	**PST250**
Max. payload	250 kg
Degree of freedom	1 axis
Nominal torque	490 Nm
Max. torque	1200 Nm
Max. tilting torque	1450 Nm
Turning range	+/-360°*
Max. rotating speed	150°/s
Repeatability	±0.05 mm**
Max. offset COG from rotating axis	200 mm
Max. mass moment of inertia	192 kgm^2
Mass	110 kg
Default height of rotating axis	545 mm***
Installation	Floor
Color	NCS S 0510-G50Y & RAL9011
Built-in utilities	Welding ground transfer system
Nominal weld current – 100% duty cycle	500 A
Environment cond.	0÷40°C (Humidity) 35÷85%, no dew

*possibility of setup range +/-36000
**on radius r=340mm from rotating axis
*** the possibility of mounting on a pedestal


3. Dimensions







A-A
1 : 5



B
1 : 5