Kawasaki Robotics

Standard specifications

PST125-L2

1st Edition: May 25, 2018

KAWASAKI HEAVY INDUSTRIES, LTD.

ROBOT DIVISION

DESIGNED AND MANUFACTURED BY ASTOR LTD.

1. Specification of positioner



- General purpose double axis positioner,
- Horizontal rotating axis + Vertical rotating axis,
- Used as an external axis with Kawasaki robots (E0x controller),
- Based on Kawasaki components and according to Kawasaki standards,
- Simple/modular body design,
- Hollow shaft – for a direct supply of energy and fluids,
- Lightweight.

2. Technical parameters

Model	**PST125-L2**
Max. payload	125 kg
Degree of freedom	2 axis
Nominal torque JT1	490 Nm
Max. torque JT1	1200 Nm
Nominal torque JT2	265 Nm
Max. torque JT2	660 Nm
Turning range JT1	+/-180°
Turning range JT2	+/-360°*
Max. rotating speed JT1	150°/s
Max. rotating speed JT2	180°/s
Repeatability	±0.05 mm**
Max. offset COG from rotating axis JT2	140 mm
Max. offset COG from flange surface	370 mm
Max. mass moment of inertia JT1	180 kgm^2
Max. mass moment of inertia JT2	80 kgm^2
Mass	330 kg
Default height of rotating axis JT1	804 mm
Installation	Floor
Color	NCS S 0510-G50Y & RAL9011
Built-in utilities	Welding ground transfer system
Nominal weld current – 100% duty cycle	500 A
Environment cond.	0÷40°C (Humidity) 35÷85%, no dew

*on radius r=340mm from rotating axis

3. Dimensions





